

DIGITAL NYLON

For application onto cotton, polyester and nylon

With an low tack adhesive carrier

DIGITAL NYLON a printable material manufactured to be used especially with nylon and waterproof fabric.

FILM COMPOSITION	PU
FILM THICKNESS	90 MICRONS
CARRIER	POLYESTER
COATING	MATT
MACHINE TESTED	ROLAND VS-640 & ROLAND SP-300
COLOUR PROFILE	GENERIC VINYL II - TTRH - THT
PRINT QUALITY	STANDARD/HIGH
MODE	PRINT & CUT
COLOUR MANAGEMENT	SIGN & DISPLAY - MAX IMPACT
HEATER	40°
DRYER	42°
BLADE	45°
MINIMUM SIZE OF CUT	1cm
OFFSET	0.25mm
PRESS TEMPERATURE	145°
PRESS TIME	12 SECONDS
PRESSURE	MEDIUM
APPLICATION TAPE REMOVAL	HOT

WASH	APPLICATION TAPE	ALL OUR FULL ROLLS ARE 25 METRES
	 YELLOW	50cm Width / 75cm Width
		Cut metres only available 50cm wide
		Other widths available on request

SUGGESTIONS

We suggest after removing the application tape, to cover the design and re-press for 2-5 seconds. This can improve the feel and texture of the transfer on the garment.

PLEASE NOTE

The technical data above are the results of our laboratory tests. We always recommend a small trial test of each product before production. We also recommend not to store the materials in damp or high temperature rooms.