

DIGITAL REFLECTIVE

For application onto cotton and polyester

With an adhesive carrier

DIGITAL REFLECTIVE is manufactured with metallized micro-beads producing an extremely high level of refraction. It is recommended to do a double print pass on this product to produce a stronger print colour.

FILM COMPOSITION	METALLIZED MICRO BEADS
FILM THICKNESS	170 MICRONS
CARRIER	POLYESTER
COATING	REFLECTIVE
MACHINE TESTED	ROLAND VS-640 & ROLAND SP-300
COLOUR PROFILE	GENERIC VINYL II - TTRH - THT
PRINT QUALITY	STANDARD/HIGH
MODE	PRINT & CUT & DOUBLE PRINT PASS
COLOUR MANAGEMENT	SIGN & DISPLAY - MAX IMPACT
HEATER	40°
DRYER	42°
BLADE	45°
MINIMUM SIZE OF CUT	1.5Cm
OFFSET	0.25mm
PRESS TEMPERATURE	150°
PRESS TIME	12 SECONDS
PRESSURE	MEDIUM
APPLICATION TAPE REMOVAL	WARM

WASH	APPLICATION TAPE	ALL OUR FULL ROLLS ARE 25 METRES
	 CLEAR	50cm Width
	 BLUE	Cut metres only available 50cm wide
		Other widths available on request

SUGGESTIONS

We suggest after removing the application tape, to cover the design and re-press for 2-5 seconds. This can improve the feel and texture of the transfer on the garment.

PLEASE NOTE

The technical data above are the results of our laboratory tests. We always recommend a small trial test of each product before production. We also recommend not to store the materials in damp or high temperature rooms.