

D-GEL

For application onto cotton and polyester

With an adhesive carrier

D-GEL is a foam material developed in our own laboratory. The film has a soft 3D effect. After pressing the film will become about 10% thinner but retain it's soft 3D effect.

FILM COMPOSITION	PU
FILM THICKNESS	750 (+/- 50) MICRONS
CARRIER	POLYESTER
COATING	MATT
MACHINE TESTED	ROLAND VS-640 & ROLAND SP-300
COLOUR PROFILE	GENERIC VINYL II - TTRH - THT
PRINT QUALITY	STANDARD/HIGH
MODE	PRINT & CUT
COLOUR MANAGEMENT	SIGN & DISPLAY - MAX IMPACT
HEATER	38°
DRYER	40°
BLADE	60°
MINIMUM SIZE OF CUT	2cm
OFFSET	0.25mm
PRESS TEMPERATURE	160°
PRESS TIME	15 SECONDS
PRESSURE	MEDIUM
APPLICATION TAPE REMOVAL	WARM

WASH	APPLICATION TAPE	ALL OUR FULL ROLLS ARE 25 METRES
	 YELLOW	50cm Width
	 RED	Cut metres only available 50cm wide
		Other widths available on request

SUGGESTIONS

AFTER REMOVING THE APPLICATION TAPE YOU MUST COVER AND RE-PRESS FOR 10 SECONDS TO ENSURE BETTER WASH RESISTANCE.

PLEASE NOTE

The technical data above are the results of our laboratory tests. We always recommend a small trial test of each product before production. We also recommend not to store the materials in damp or high temperature rooms.